

Guideline xml - DespatchAdvice-TransportAdvice

Element/Attribute	Description	Usage
DespatchAdvice	Type DespatchAdviceType	
— cbc:UBLVersionID	Occurrence 1 .. 1 Type cbc:UBLVersionIDType Fixed value: 2.1	
— cbc:CustomizationID	Occurrence 1 .. 1 Type cbc:CustomizationIDType Fixed value: urn-x:sfti:documents:schema:xsd:DespatchAdvice_TransportAdvice-1:ver1.0	
— cbc:ProfileID	Occurrence 1 .. 1 Type cbc:ProfileIDType Fixed value: urn:sfti:services:documentprocessing:DespatchAdvice_TransportAdvice:1:0	
— cbc:ID	Occurrence 1 .. 1 Type cbc:IDType	Usage Definition <i>Document identifier</i> An transaction instance must contain an identifier. The identifier enables positive referencing the document instance for various purposes including referencing between transactions that are part of the same process.
— cbc:IssueDate	Occurrence 1 .. 1 Type cbc:IssueDateType	Usage <i>DespatchAdvice-TransportAdvice issue date</i>
— cbc:IssueTime	Occurrence 0 .. 1 Type cbc:IssueTimeType	Usage <i>Despatch advice-TransportAdvice issue time</i>
— cbc:Note	Occurrence 0 .. 1 Type cbc:NoteType	Definition A textual note for the despatch as whole.
— cac:DespatchSupplierParty	Occurrence 1 .. 1 Type cac:SupplierPartyType	Usage <i>Avsändare. Ofta leverantören.</i>
— cac:Party	Occurrence 1 .. 1 Type cac:PartyType	Usage <i>Despatching party</i>
— cac:PartyIdentification	Occurrence 0 .. 1 Type cac:PartyIdentificationType	
— cbc:ID	Occurrence 1 .. 1 Type cbc:IDType	Usage <i>Despatching party identifier. GLN</i>
— <i>schemeID</i>	Type <i>xs:normalizedString</i> Use <i>optional</i>	
— cac:PartyName	Occurrence 0 .. 1 Type cac:PartyNameType	
— cbc:Name	Occurrence 1 .. 1 Type cbc:NameType	Usage <i>Despatching party name</i>
— cac:Contact	Occurrence 0 .. 1 Type cac:ContactType	Usage <i>Despatching party contact information to a person.</i>
— cbc:Name	Occurrence 0 .. 1 Type cbc:NameType	

Bold = Element, Italic = Attribute

Element/Attribute	Description	Usage
cbc:Telephone	Occurrence 0 .. 1 Type cbc:TelephoneType	
cbc:ElectronicMail	Occurrence 0 .. 1 Type cbc:ElectronicMailType	
cac:DeliveryCustomerParty	Occurrence 1 .. 1 Type cac:CustomerPartyType	Usage Mottagare av leverans. Consignee. Distributionscentral.
cac:Party	Occurrence 1 .. 1 Type cac:PartyType	
cbc:EndpointID	Occurrence 0 .. 1 Type cbc:EndpointIDType	
<i>schemeID</i>	Type <i>xs:normalizedString</i> Use <i>optional</i>	
cac:PartyIdentification	Occurrence 0 .. 1 Type cac:PartyIdentificationType	
cbc:ID	Occurrence 1 .. 1 Type cbc:IDType	Usage Consignee party identifier. Id till Distributionscentralen.
<i>schemeID</i>	Type <i>xs:normalizedString</i> Use <i>optional</i>	
cac:PartyName	Occurrence 0 .. 1 Type cac:PartyNameType	
cbc:Name	Occurrence 1 .. 1 Type cbc:NameType	Usage Consignee party name. Namn på Distributionscentralen.
cac:PostalAddress	Occurrence 0 .. 1 Type cac:AddressType	Usage Consignee party adress. Distributionscentralen.
cbc:ID	Occurrence 0 .. 1 Type cbc:IDType	
<i>schemeID</i>	Type <i>xs:normalizedString</i> Use <i>optional</i>	
cbc:StreetName	Occurrence 0 .. 1 Type cbc:StreetNameType	
cbc:AdditionalStreetName	Occurrence 0 .. 1 Type cbc:AdditionalStreetNameType	
cbc:CityName	Occurrence 0 .. 1 Type cbc:CityNameType	
cbc:PostalZone	Occurrence 0 .. 1 Type cbc:PostalZoneType	
cbc:CountrySubentityCode	Occurrence 0 .. 1 Type cbc:CountrySubentityCodeType	
cac:Country	Occurrence 0 .. 1 Type cac:CountryType	
cbc:IdentificationCode	Occurrence 0 .. 1 Type cbc:IdentificationCodeType	Definition Usage listID="ISO3166-1:Alpha2" Country code
<i>listID</i>	Type <i>xs:normalizedString</i>	

Bold = Element, Italic = Attribute

Element/Attribute	Description	Usage
cac:DeliveryContact	<i>Use optional</i> Occurrence 0 .. 1 Type cac:ContactType	Usage Definition Consignment party contact information to a person. Kontaktperson på Distributionscentralen.
cbc:Name	Occurrence 0 .. 1 Type cbc:NameType	
cbc:Telephone	Occurrence 0 .. 1 Type cbc:TelephoneType	
cbc:ElectronicMail	Occurrence 0 .. 1 Type cbc:ElectronicMailType	
cac:BuyerCustomerParty	Occurrence 0 .. 1 Type cac:CustomerPartyType	Usage Köparen
cac:Party	Occurrence 1 .. 1 Type cac:PartyType	
cac:PartyIdentification	Occurrence 0 .. 1 Type cac:PartyIdentificationType	
cbc:ID	Occurrence 1 .. 1 Type cbc:IDType	Usage Buying party identification. GLN
<i>schemeID</i>	Type xs:normalizedString <i>Use optional</i>	
cac:PartyName	Occurrence 0 .. 1 Type cac:PartyNameType	
cbc:Name	Occurrence 1 .. 1 Type cbc:NameType	
cac:SellerSupplierParty	Occurrence 0 .. 1 Type cac:SupplierPartyType	Usage Leverantören. Om leverantören och avsändaren (DespatchSupplierParty) är samma part, kan denna uppgift utelämnas.
cac:Party	Occurrence 1 .. 1 Type cac:PartyType	
cac:PartyIdentification	Occurrence 0 .. 1 Type cac:PartyIdentificationType	
cbc:ID	Occurrence 1 .. 1 Type cbc:IDType	Usage Seller party Identification. GLN
<i>schemeID</i>	Type xs:normalizedString <i>Use optional</i>	
cac:PartyName	Occurrence 0 .. 1 Type cac:PartyNameType	
cbc:Name	Occurrence 1 .. 1 Type cbc:NameType	Usage Seller party name.
cac:Contact	Occurrence 0 .. 1 Type cac:ContactType	Usage Definition Seller party contact information to a person. Kontaktperson hos leverantören.
cbc:Name	Occurrence 0 .. 1 Type cbc:NameType	

Bold = Element, Italic = Attribute

Element/Attribute	Description	Usage
cbc:Telephone	Occurrence 0 .. 1 Type cbc:TelephoneType	
cbc:ElectronicMail	Occurrence 0 .. 1 Type cbc:ElectronicMailType	
cac:Shipment	Occurrence 1 .. 1 Type cac:ShipmentType	Usage Definition <i>Leveransen</i> Description of the actual shipment that contains the goods that are being despatched.
cbc:ID	Occurrence 1 .. 1 Type cbc:IDType	Usage Definition <i>Shipment identifier. If possible use G SIN.</i> In some uses of the Despatch Advice, there is no unique identifier assigned to the shipment. However, the UBL syntax requires the Shipment ID. In this case a dummy value must be used and consist of the characters NA
cbc:HandlingCode	Occurrence 0 .. 1 Type cbc:HandlingCodeType	Usage <i>Hantering av leveransen i kodform.</i>
listID	Type xs:normalizedString Use optional	
cbc:HandlingInstructions	Occurrence 0 .. unbounded Type cbc:HandlingInstructionsType	Usage Definition <i>Hantering av leveransen.</i> Ange om någon del av leveransen ska hanteras med restriktion på värme. Använd något av Kyl/Frys/Värme
cbc:GrossWeightMeasure	Occurrence 0 .. 1 Type cbc:GrossWeightMeasureType	Usage Definition <i>Bruttovikt för hela leveransen</i> The total weight of the shipment including packaging, as dispatched from the despatching party.
unitCode	Type xs:normalizedString Use required	
cbc:GrossVolumeMeasure	Occurrence 0 .. 1 Type cbc:GrossVolumeMeasureType	Usage Definition <i>Bruttovolym för hela leveransen</i> The total volume of the shipment including packaging, as dispatched from the despatching party.
unitCode	Type xs:normalizedString Use required	
cbc:TotalTransportHandlingUnitQuantity	Occurrence 0 .. 1 Type cbc:TotalTransportHandlingUnitQuantityType	Usage <i>Totalt antal Transportkoll i leveransen</i>
cac:Consignment	Occurrence 0 .. 1 Type cac:ConsignmentType	
cbc:ID	Occurrence 1 .. 1 Type cbc:IDType	Usage Definition <i>Consignment identifier</i> An association to Consignment covering the shipment. Unique number assigned to goods, both for import and export. Specified by the shipper. If possible, use G INC.
cbc:Information	Occurrence 0 .. unbounded Type cbc:InformationType	Usage Definition <i>Vehicle description</i> Description and/or identification of the vehicle that transports the despatched shipment.
cac:CarrierParty	Occurrence 0 .. 1	Usage <i>Transportör</i>

Bold = Element, Italic = Attribute

Element/Attribute	Description	Usage
cac:PartyName	Type cac:PartyType Occurrence 0 .. 1	
<i>cbc:Name</i>	Type cac:PartyNameType Occurrence 1 .. 1	Term name Carrier name Definition The name of the carrier that handles the delivery of the despatched shipment.
cac:Person	Occurrence 0 .. 1 Type cac:PersonType	Usage <i>Föraren</i>
cac:IdentityDocumentReference	Occurrence 1 .. 1 Type cac:DocumentReferenceType	Usage <i>Förarens körkort/id</i>
<i>cbc:ID</i>	Occurrence 1 .. 1 Type cbc:IDType	Usage <i>Driver information</i> Definition Identification about the driver of the vehicle that delivers the despatched shipment
<i>cbc:DocumentType</i>	Occurrence 0 .. 1 Type cbc:DocumentTypeType	Usage <i>Driver identification document type</i> Definition The type of document used for identifying the driver, expressed in text. Ex vis Körkort
cac:Delivery	Occurrence 1 .. 1 Type cac:DeliveryType	
<i>cbc:TrackingID</i>	Occurrence 0 .. 1 Type cbc:TrackingIDType	Usage <i>Delivery tracking identifier</i> Definition Used to provide a tracking id for delivery e.g. UPS or postal.
cac:EstimatedDeliveryPeriod	Occurrence 0 .. 1 Type cac:PeriodType	Usage <i>Leveransperiod till DC</i>
<i>cbc:StartDate</i>	Occurrence 0 .. 1 Type cbc:StartDateType	
<i>cbc:StartTime</i>	Occurrence 0 .. 1 Type cbc:StartTimeType	
<i>cbc:EndDate</i>	Occurrence 0 .. 1 Type cbc:EndDateType	
<i>cbc:EndTime</i>	Occurrence 0 .. 1 Type cbc:EndTimeType	
cac:Despatch	Occurrence 0 .. 1 Type cac:DespatchType	
<i>cbc:ActualDespatchDate</i>	Occurrence 0 .. 1 Type cbc:ActualDespatchDateType	Usage <i>Shipment dispatch date</i> Definition The actual or expected date when the shipment was despatched from the despatching party.
<i>cbc:ActualDespatchTime</i>	Occurrence 0 .. 1 Type cbc:ActualDespatchTimeType	Usage <i>Shipment dispatch time</i> Definition The actual or expected time when the shipment was despatched from the despatching party.
cac:TransportHandlingUnit	Occurrence 1 .. unbounded Type cac:TransportHandlingUnitType	Usage <i>Transportkoll</i>

Bold = Element, Italic = Attribute

Element/Attribute	Description	Usage
cbc:ID	Occurence 1 .. 1 Type cbc:IDType	Usage Definition <i>Transportkollits identitet (SSCC)</i> Om Transportkollit saknas (löst kollit), ange "NA". Det "lösa" kollit anges som vanligt i Package
<i>schemeID</i>	<i>Type</i> xs:normalizedString <i>Use</i> optional	
cbc:TransportHandlingUnitTypeCode	Occurence 0 .. 1 Type cbc:TransportHandlingUnitTypeCodeType	Usage Definition <i>Handling unit type. Typ av kollit</i> The type of packaging that represent the handling unit, such as box, pallet, container etx. Usage <i>listID=UNECERec21</i>
<i>listID</i>	<i>Type</i> xs:normalizedString <i>Use</i> optional	
cbc:HandlingCode	Occurence 0 .. 1 Type cbc:HandlingCodeType	Usage <i>Hantering av leveransen i kodform.</i>
<i>listID</i>	<i>Type</i> xs:normalizedString <i>Use</i> optional	
cbc:HandlingInstructions	Occurence 0 .. unbounded Type cbc:HandlingInstructionsType	Usage Definition <i>Hantering av kollit.</i> Ange om någon del av kollit ska hanteras med restriktion på värme. Använd något av Kyl/Frys/Värme
cbc:HazardousRiskIndicator	Occurence 0 .. 1 Type cbc:HazardousRiskIndicatorType	Usage Definition <i>Farligt gods indikator</i> Indicates whether the transportunit contains hazardous materials
cbc:TotalPackageQuantity	Occurence 0 .. 1 Type cbc:TotalPackageQuantityType	Usage <i>Totalt antal kollit (Packages) i detta Transportkollit</i>
cac:MeasurementDimension	Occurence 0 .. unbounded Type cac:DimensionType	
cbc:AttributeID	Occurence 1 .. 1 Type cbc:AttributeIDType	Definition Handling gross weight, including packaging as despatched by despatching party. Handling gross volume, including packaging as despatched by despatching party. "AAB" for Unit gross weight and "AAW" for Gross volume Usage <i>Vikt och volymsinformation för transportkollit</i> Usage <i>schemeID=UNECERec20</i>
<i>schemeID</i>	<i>Type</i> xs:normalizedString <i>Use</i> optional	
cbc:Measure	Occurence 0 .. 1 Type cbc:MeasureType	Usage <i>Transportkollits nettovikt, bruttovikt vikt inkl förpackning men exkl lastbärare och bruttovolym</i>
<i>unitCode</i>	<i>Type</i> xs:normalizedString <i>Use</i> required	
cac:MinimumTemperature	Occurence 0 .. 1 Type cac:TemperatureType	Usage Definition <i>Minimum storage temperature</i> The lower margin of the recommended storage temperature range for the item <i>Används vid behov då Kyl/Frys/Värme inte räcker</i>

Bold = Element, Italic = Attribute

Element/Attribute	Description	Usage
cbc:AttributeID	Occurrence 1 .. 1 Type cbc:AttributeIDType	Definition "TC" for Temperature Usage <i>schemeID=UNECERec20</i>
cbc:Measure	Occurrence 1 .. 1 Type cbc:MeasureType	Usage <i>Minimum storage temperature</i>
<i>unitCode</i>	Type <i>xs:normalizedString</i> Use <i>required</i>	
cac:MaximumTemperature	Occurrence 0 .. 1 Type cac:TemperatureType	Usage <i>Vid behov maximala temperatur</i> Definition The upper margin of the recommended storage temperature range for the item Används vid behov då Kyl/Frys/Värme inte räcker
cbc:AttributeID	Occurrence 1 .. 1 Type cbc:AttributeIDType	Definition "TC" for Temperature Usage <i>schemeID=UNECERec20</i>
cbc:Measure	Occurrence 1 .. 1 Type cbc:MeasureType	Usage <i>Maximum storage temperature</i>
<i>unitCode</i>	Type <i>xs:normalizedString</i> Use <i>required</i>	
cac:Package	Occurrence 1 .. unbounded Type cac:PackageType	Usage <i>Kolli</i>
cbc:ID	Occurrence 1 .. 1 Type cbc:IDType	Usage <i>Kollits identitet (SSCC)</i>
<i>schemeID</i>	Type <i>xs:normalizedString</i> Use <i>optional</i>	
cbc:PackagingTypeCode	Occurrence 0 .. 1 Type cbc:PackagingTypeCodeType	Usage <i>Handling unit type. Typ av kolli</i> Definition The type of packaging that represent the handling unit, such as box, pallet, container etc. Usage <i>listID=UNECERec21</i>
<i>listID</i>	Type <i>xs:normalizedString</i> Use <i>optional</i>	
cac:GoodsItem	Occurrence 0 .. unbounded Type cac:GoodsItemType	Usage <i>Artikel/artiklar som finns i kollit.</i>
cbc:HazardousRiskIndicator	Occurrence 0 .. 1 Type cbc:HazardousRiskIndicatorType	Usage <i>Hazardous indicator</i> Definition Indicates whether the item is hazardous
cac:InvoiceLine	Occurrence 0 .. unbounded Type cac:InvoiceLineType	
cbc:ID	Occurrence 1 .. 1 Type cbc:IDType	Usage <i>Ange värdet NA</i>
cbc:LineExtensionAmount	Occurrence 1 .. 1 Type cbc:LineExtensionAmountType	
<i>currencyID</i>	Type <i>xs:normalizedString</i> Use <i>required</i>	
cac:OrderLineReference	Occurrence 1 .. unbounded Type cac:OrderLineReferenceType	Usage <i>Order line reference</i> Definition To uniquely identify the line of the order that is being despatched.

Bold = Element, Italic = Attribute

Element/Attribute	Description	Usage
cbc:LineID	Occurrence 1 .. 1 Type cbc:LineIDType	Usage Kundens/Köparens orderradsnummer. Om okänd anges värdet 0 Definition To uniquely identify the line of the order that is being despatched.
cac:OrderReference	Occurrence 1 .. 1 Type cac:OrderReferenceType	
cbc:ID	Occurrence 1 .. 1 Type cbc:IDType	Usage Kundens/Köparens ordernummer Definition To uniquely identify the order that is being despatched.
cac:DocumentReference	Occurrence 0 .. unbounded Type cac:DocumentReferenceType	
cbc:ID	Occurrence 1 .. 1 Type cbc:IDType	Usage Följesedelnummer
cbc:DocumentTypeCode	Occurrence 0 .. 1 Type cbc:DocumentTypeCodeType	Usage Ange värdet 700 för följesedel (waybill). <i>listID="UN/ECE 1001"</i>
<i>listID</i>	Type xs:normalizedString Use optional	
cac:Item	Occurrence 1 .. 1 Type cac:ItemType	
cbc:Name	Occurrence 1 .. 1 Type cbc:NameType	
cac:HazardousItem	Occurrence 0 .. unbounded Type cac:HazardousItemType	
cbc:UNDGCode	Occurrence 0 .. 1 Type cbc:UNDGCodeType	Usage <i>UNDG-Kod för Farligt gods</i> Definition The identifier assigned to transportable hazardous goods by the United Nations, expressed as a code.
<i>listID</i>	Type xs:normalizedString Use required	Usage <i>listID="UNCL8273"</i>
<i>listAgencyID</i>	Type xs:normalizedString Use optional	
<i>listAgencyName</i>	Type xs:string Use optional	
<i>listVersionID</i>	Type xs:normalizedString Use optional	
<i>name</i>	Type xs:string Use optional	
cbc:HazardClassID	Occurrence 0 .. 1 Type cbc:HazardClassIDType	Usage <i>Hazardous hazard class Identifier</i> Definition Identifies a hazard class applicable to dangerous goods as defined by the relevant regulation authority, such as the IMDG Class Number of the SOLAS Convention of IMO and the ADR/RID Class Number for the road/rail environment.
<i>schemeID</i>	Type xs:normalizedString Use optional	
<i>schemeAgencyID</i>	Type xs:normalizedString	

Bold = Element, Italic = Attribute

Element/Attribute	Description	Usage
<i>schemeAgencyName</i>	Use optional Type xs:string	
cac:MeasurementDimension	Use optional Occurrence 0 .. unbounded Type cac:DimensionType	Usage Kollits bruttovikt, nettovikt och bruttovolym och max/min temperatur
cbc:AttributID	Occurrence 1 .. 1 Type cbc:AttributIDType	Definition Handling gross weight, including packaging as despatched by despatching party. Handling gross volume, including packaging as despatched by despatching party. "AAA" for Unit net weight "AAB" for Unit gross weight "AAW" for Gross volume "TC" for temperature
<i>schemeID</i>	Type xs:normalizedString Use optional	Usage Usage Vikt, volymsinformation och temperatur för kollit <i>schemeID=UNECERec20</i>
cbc:Measure	Occurrence 0 .. 1 Type cbc:MeasureType	Usage Kollits nettovikt, bruttovikt vikt inkl förpackning men exkl lastbärare och bruttovolym
<i>unitCode</i>	Type xs:normalizedString Use required	
cbc:MinimumMeasure	Occurrence 0 .. 1 Type cbc:MinimumMeasureType	Usage Minimum storage temperature Definition The lower margin of the recommended storage temperature range for the transport unit. Används vid behov för att informera om Kyl/Frys/Värme restriktioner för kollit
<i>unitCode</i>	Type xs:normalizedString Use required	
cbc:MaximumMeasure	Occurrence 0 .. 1 Type cbc:MaximumMeasureType	Usage Maximum storage temperature Definition The upper margin of the recommended storage temperature range for the transport unit. Används vid behov för att informera om Kyl/Frys/Värme restriktioner för kollit
<i>unitCode</i>	Type xs:normalizedString Use required	
cac:Delivery	Occurrence 1 .. 1 Type cac:DeliveryType	
cac:DeliveryLocation	Occurrence 1 .. 1 Type cac:LocationType	Usage Slutmottagare, GLN, Namn, Adress
cbc:ID	Occurrence 0 .. 1 Type cbc:IDType	Usage Delivery location identifier. GLN till slutmottagare.
<i>schemeID</i>	Type xs:normalizedString Use optional	

Bold = Element, Italic = Attribute

Element/Attribute	Description	Usage
cbc:Name	Occurrence 0 .. 1 Type cbc:NameType	
cac:Address	Occurrence 0 .. 1 Type cac:AddressType	
cbc:StreetName	Occurrence 0 .. 1 Type cbc:StreetNameType	
cbc:CityName	Occurrence 0 .. 1 Type cbc:CityNameType	
cbc:PostalZone	Occurrence 0 .. 1 Type cbc:PostalZoneType	
cac:Country	Occurrence 0 .. 1 Type cac:CountryType	
cbc:IdentificationCode	Occurrence 0 .. 1 Type cbc:IdentificationCodeType	Usage Country Code Definition listID="ISO3166-1:Alpha2"
<i>listID</i>	Type xs:normalizedString Use optional	
cac:RequestedDeliveryPeriod	Occurrence 0 .. 1 Type cac:PeriodType	Usage Önskat leveransdatum (period) slutmottagaren
cbc:StartDate	Occurrence 0 .. 1 Type cbc:StartDateType	
cbc:StartTime	Occurrence 0 .. 1 Type cbc:StartTimeType	
cbc:EndDate	Occurrence 0 .. 1 Type cbc:EndDateType	
cbc:EndTime	Occurrence 0 .. 1 Type cbc:EndTimeType	
cac:DespatchLine	Occurrence 1 .. 1 Type cac:DespatchLineType	Usage Obligatoriskt i UBL. Används inte i detta meddelande. Usage Ange 0 i ID
cbc:ID	Occurrence 1 .. 1 Type cbc:IDType	Usage Obligatoriskt i UBL. Används inte i detta meddelande. Usage Ange 0
cac:OrderLineReference	Occurrence 1 .. unbounded Type cac:OrderLineReferenceType	Usage Obligatoriskt i UBL. Används inte i detta meddelande. Uppgifterna anges för varje kolla (Package).
cbc:LineID	Occurrence 1 .. 1 Type cbc:LineIDType	Usage Obligatoriskt i UBL. Används inte i detta meddelande. Uppgifterna anges för varje kolla (Package). Usage Ange 0
cac:Item	Occurrence 1 .. 1 Type cac:Item	Usage Används inte. Men är obligatoriskt i UBL Usage Lämna tomt.

Bold = Element, Italic = Attribute